

1. INSTALLATION PER CITY OF CHANDLER STREET LIGHTING STANDARDS AND SPECIFICATIONS.
2. THE DEVELOPER SHALL COORDINATE ALL STREET LIGHT PLANS WITH APS. CONTACT THE APS CUSTOMER SERVICE REPRESENTATIVE OFFICE AT 602-493-4433.
3. THE CONTRACTOR WILL COORDINATE HIS WORK WITH THE APS LIGHTING DIVISION PRIOR TO THE START OF CONSTRUCTION.
4. STREET LIGHT CONDUCTOR TRENCHES WILL NOT BE BACKFILLED UNTIL INSPECTED AND APPROVED BY OFFSITE INSPECTOR.
5. DESIGNS IN CONFORMANCE WITH APPENDIX "A" OF THE STREET LIGHT STANDARDS SPECIFY G.E. POWER DOOR SERIES LUMINARE. APPROVED EQUALS ARE LISTED IN THE DESIGN MANUAL.
6. ANY VARIANCE TO AN APPROVED LUMINARE SHALL REQUIRE A NEW DESIGN ACCOMPANIED WITH POINT-TO-POINT LIGHTING CALCULATIONS AT TEN FOOT INTERVALS INDICATING MAINTAINED FOOTCANDLE LEVELS BETWEEN LUMINARIES AND ACROSS THE WIDTH OF THE ROADWAY FOR APPROVAL BY THE CITY ENGINEER.
7. POLES SHALL BE SET NO CLOSER THAN SIX (6) FEET FROM FACE OF CURB.
8. THE JUNCTION BOX NEAREST A POLE SHALL BE LOCATED OUT OF THE PUBLIC RIGHT-OF-WAY IN A PUBLIC UTILITY EASEMENT UNLESS OTHERWISE DIRECTED.